

# TTH 311 SELF-CONTAINED EMERGENCY LUMINAIRES ( LED )



**Dimension** : 88L x 95 Diameter (125 Diameter available)

## SPECIFICATION

|                           |  |
|---------------------------|--|
| <b>Model</b>              | : TTH 311  |
| <b>System Mode</b>        | : Non Maintained   |
| <b>Emergency Duration</b> | : 2 hours (3 hours available)  |
| <b>Lamp</b>               | : 1W High Output white L.E.D.  |
| <b>Battery</b>            | : 2.4V 1.6AH High temperature nickel cadmium battery   |
| <b>Recharge period</b>    | : 16 fi 24 hours   |
| <b>Battery Protection</b> | : Low Voltage cut off to prevent from over charging  |
| <b>Monitoring</b>         | : Green L.E.D. †ON† indicates charging<br>Equipped with push test switch to simulate power failure |
| <b>Input Voltage</b>      | : 240V 50Hz  |
| <b>Charger</b>            | : Constant current   |
| <b>Housing</b>            | : Fire retardant ABS housing   |
| <b>Dimension</b>          | : 88L x 95 Diameter (125 Diameter available)   |
| <b>Weight</b>             | : 0.35 kg  |
| <b>Mounting</b>           | : Recess mounted from ceiling (Surface mounted available)  |
| <b>Warranty</b>           | : 1 Year   |
| <b>Compliance</b>         | : SS 563 : 2010, SS 263 PART 2 : 1998  |

Note : Due to continuous development and improvement, our company reserves the right to change specifications without notice.